

SCANNING DEVICES		PROOFING DEVICES	
FLATBED SCANNER MAX. COPY SIZE 16" x 22" MAX. SCAN AREA 12.5" x 20"	DRUM SCANNER MAX. COPY SIZE 21" x 27" MAX. SCAN AREA 19" x 26"	EPSON MAX. SIZE 43.76" image on 44" stock x the length of material	FUJI PICTRO MAX. SIZE 12.2" x 18" FUJI FINAL PROOF MAX. SIZE 20.9" x 26.6"

PRESSROOM EQUIPMENT							
PRESS	DESCRIPTION	MIN. PAPER SIZE	MAX. PAPER SIZE	GRIP MARGIN	MAX. IMAGE AREA	STOCK RANGE	MISC.
HALM SUPER JET	2/2 ENVELOPE PRESS	3.25" x 4.25"	12" x 18"	-----	12" x 18" S 9.375" x 12" P	20# BOND ---12PT .0035---.012	
HEIDELBERG SPEEDMASTER 52	2/0 OR 1/1 PERFECTOR	4.125" x 5.6875" 4.125" x 5.5" WHEN PERFECTING	14.5625" x 20.5"	.375"	14.1875" x 20.5" P 13.75" x 20.5" P	.0016---.016	
HEIDELBERG* MOZP	2/0 OR 1/1 PERFECTOR	8.25" x 11" 11" x 11" WHEN PERFECTING	19" x 25.5"	.375"	18.578125" x 25.375" S 18.25" x 25.375" P	ONIONSKIN--24PT .0016---.024	
SHINOHARA IIP	2/0 OR 1/1 PERFECTOR	7.875" x 11.75" 7.875" x 10.125" WHEN PERFECTING	19" x 25"	.375"	18.5" x 25.5656"	.0016---.024 S .0016---.012 P	
KOMORI LITHRONE S40*	6/0 W/AQUEOUS	14.1875" x 20.5"	28.375" x 40.5625"	.075 MIN. 1" PREFERRED	27.9375" x 40.1875"	UP TO .040	
KOMORI LITHRONE S40 W/UV*	6/0 UV INK W/UV COATING	14.1875" x 20.5"	28.375" x 40.5625"	.075 MIN. 1" PREFERRED	27.9375" x 40.1875"	UP TO .040	
KOMORI SYSTEM 20	6/6 PERFECTOR	14.1875" WEB WIDTH	20" WEB WIDTH	.375" IMAGE FREE AREA	19.875" x 22.625" (INCLUDES THE COLOR BAR)	.002---.012	50# COATED AND ABOVE CAN BE SHEETED. 3" CORE UP TO 50" DIAMETER ROLLS
*BATCH TABBER	MOBILE IN-LINE TABBER FOR THE MO 2 COLOR AND KOMORI S-40'S						

DIGITAL PRINTING CAPABILITIES							
PRESS	DESCRIPTION	MIN. PAPER SIZE	MAX. PAPER SIZE	GRIP MARGIN	MAX. IMAGE AREA	STOCK RANGE	MISC.
XEROX DOCUTECH 6135	1 COLOR	8" x 10"	11" x 17"	-----	11" x 17"	.003---.009	IN-LINE THERMAL BINDING, COLLATING, CORNER & SIDE STITCHING
XEROX DOCUCOLOR 240	4 COLOR	8.5" x 5.5"	13" x 19"	-----	12.5" x 18.9"	.003---.010	

LETTERPRESS							
PRESS	DESCRIPTION	MIN. PAPER SIZE	MAX. PAPER SIZE	GRIP MARGIN	MAX. IMAGE AREA	STOCK RANGE	MISC.
V-50	CYLINDER DIECUTTER, NUMBERING MACHINE	3.25" x 5.5"	14" x 20"	.25"	-----	.002---.015	
BRAUSSE	PLATEN DIECUTTER	14.5" x 15.75"	29.5" x 41.125"	.375"	-----	.0039---.078	IN-LINE TABBING WHEN SIZED IN 1/2" LIFTS OR MORE

BINDERY EQUIPMENT								
POLAR GUILLOTINE CUTTERS (5) MAX. WIDTH/DEPTH 45.25" MBO FOLDERS MIN. 4" x 6" MAX. 30" x 44" MIN. FIRST FOLD LENGTH 2.125" MBO Z2 KNIFE FOLD UNIT MIN. 3.125" x 6" MAX. 12.5" x 19.5" Can be added to the Muller Martini for in-line soft folding MULLER MARTINI MINUTE MAN 8 pockets plus cover feeder saddle stitcher Standard and loop stitches (up to 4 standard or 3 loop heads per pass) The min. distance between the outside of two stitches is 3.5" MIN. TRIMMED BOOK SIZE 3.5" x 5.5625" MAX. TRIMMED BOOK SIZE 11.8125" x 15" MULLER MARTINI BRAVO M 8 pockets plus cover feeder saddle stitcher Standard and loop stitches (up to 4 standard or 3 loop heads per pass). The min. distance between the outside of two stitches is 3.5". 5 knife trimming capabilities .25" and .3125" gutter cuts. 3-hole in-line drilling capabilities – used for quantities over 50M and on books less than 1" thick (1/4" or 5/16" hole) Min. spine length for in-line drilling is 10.625" (i.e. 8" x 10" doesn't work).	MIN. MAX. 1-up format 3" x 4.5" 11.75" x 18" Double up 3" x 3.5" 11.75" x 18" For feeding into the trimmer, the min. spine to face dimension must be at least 4.3125"		VACUUMATIC TABBER MIN. MAX. 4" X 2.25" 30" x 30" BAUM DRILL 1-5 holes plus round corner capabilities .125"-.5" drill punches .1875", .375", .5" radius round corner dies SHANKLIN WRAPPER MIN. MAX. — 16" x 20" x 5"		STANDARD MC-80 COLLATOR (COLLATOR/BOOKLET MAKER - 32 POCKET COLLATOR) When booklet making, the Standard will collate, stitch, fold and face trim. Head and foot trims must be cut on the guillotine. For booklet making, the maximum number of pages of 20# stock is (64 pg. s/c). This restriction is due to the machine's limitations for stitching and folding thickness. STRAIGHT STACKING MIN. FLAT MAX. FLAT 5.75" x 8.25" 12.25" x 18.5" CORNER/SIDE/TOP STITCHING MIN. MAX. 5.75" x 8.25" 13" x 14.25" BOOKLET MAKING MIN. MAX. 8" x 8" 12.5" x 18.5"		VIDEOJET INK JET MIN. MAX. MIN. THICKNESS MAX. THICKNESS 3" x 5" 17" x 17" .0035" 1" Number of heads per line: 8 Number of lines to print: 18+barcode Number of heads for numbering: 8 BUSKRO 530 TABBER MIN. MAX. MIN. THICKNESS MAX. THICKNESS 3" x 5" 16" x 17" .0035" .625" Number of tabs in line: 3 Tabber roll core diameter: 3" Tabber spool max. diameter: 19.75" Tab length: .75" to 2" Tab width: Up to 2" Tab styles: Circle, square, rectangle, stamps Tab placement: Left, right, or flat	
	KLUGE UNIFOLD (POCKET FOLDER GLUER) MIN. MAX. STOCK RANGE 6" x 6" 29" x 24" .006 - .018 KANSA PADDER MIN. MAX. MAX. THICKNESS 2" x 2" 28" x 14" 1"	MAIL LIST DATA BASES IBM Compatible text base – ASCII, Access, Excel						